

COLD WATER MOBILE TRAILER


FRAME

HONDA® GX390 ENGINE

Equipped with low oil shutdown feature with recoil & e-start

PREMIUM 6-PLY TIRES

For increased mobility across various terrains



STEEL-BRAIDED **MONSTER HOSE**

Kink and abrasion resistant hose with quick connect fittings and polyurethane outer jacket

INDUSTRIAL TRIPLEX

With external unloader and bypass hose

49-State DOES NOT SHIP to CA **PART#** 95003

PRESSURE RATING: 4200 PSI

FLOW RATING: 4.0 GPM

ENGINE: HONDA® GX390 Recoil & E-Start

LOW OIL

PUMP: CAT PUMPS® Industrial Triplex

TRAILER SIZE: 9' Overall (4'x 5'6" Platform)

TRAILER FRAME: Rectangular think wall steel tubing

AXLE RATING: 2000 lbs

TIRE: 5.30" - 12"

LIGHTING: LED

TRAILER HITCH BALL SIZE: 2" ball

WATER TANK SIZE: 150 gal

HIGH PRESSURE HOSE: 3/8" x 100' Monster Hose

HIGH PRESSURE HOSE REEL: 100'

SUPPLY HOSE: N/A

SUPPLY REEL: N/A

DIMENSIONS / WEIGHT: L:80" x W:52" x H:72" | 630 lbs

LIMITED PRODUCT WARRANTIES



5 YEAR PUMP WARRANTY

1 YEAR FRAME WARRANTY







